

FF-201 FF-203 FF-207 Optical Fiber Multimeter

Features

- 1) Support Background Light on/off
- 2) Support Auto Shut Down to Save Power
- 3) dBm/mW Simultaneously Display
- 4) Users can calibrate it
- 5) 2.5mm universal connector for FC/SC/LC Connectors
- 6) Compact appearance, easy to carry

Specification

<i>Optical Power Meter (OPM)</i>	
Wavelength Range	800nm to 1700nm
Connector	2.5mm Universal Connector
Detector Type	InGaAs
Power Range	-70 to +6dBm
Uncertainty	±5%
Calibrated Wavelength	850/980/1300/1310/1490/1550/1625/1650nm
Display Resolution	Linear Resolution 0.1% Logarithmic Resolution 0.01dBm
<i>Visual Fault Locator (VFL)</i>	
Wavelength	650nm
Output Power	2mW
Mode	CW/1Hz/2Hz
Connector	2.5mm Universal
<i>RJ45 Cable Sequence Test</i>	
Cable Length	<300m
Remote Unit	Yes
<i>General</i>	
Power Supply	AAA Battery
Auto Shutdown	10 mins
Operation Temperature	-10 to +50 °C
Storage Temperature	-40 to +70 °C
Relative Humidity	0 ~ 95% no condensing
Size	112x66x30mm



ORDERING INFORMATION

FF-201	OPM
FF-203	OPM & VFL
FF-207	OPM, VFL & Rj45